

X3 Pro

\$727.00

\$1,219.00

\$519.00

\$869.00

X3R

\$979.00

\$1,399.00

\$699.00

\$999.00

X4R

\$1,119.00

\$1,679.00

\$1,199.00

\$799.00

X8R

\$1,259.00

\$1,819.00

\$899.00

\$1,299.00

X3

\$699.00

\$1,189.00

\$499.00

\$849.00

X4 Sport

\$685.00

\$489.00

\$839.00

\$1,179.00

Model Name

MSRP Price (Standard SLA Battery)

MSRP Price (LI Battery)

Sale Price (Standard SLA Battery)

Sale Price (LI Battery)

X4 Classic

\$559.00

\$1,049.00

\$399.00

\$749.00

Standard Battery	22Ah SLA Dim: 7.5 x 6.5 x 3 in (19 x 17 x 8 cm) Weight 15 Lbs (6.8 kg) Average charge time: 4-8 hours Performance/Charge: 27+ Holes Lifetime: ca. 150+ charges	33Ah SLA Dim: 8 x 5 x 6 in (20 x 13 x 15 cm) Weight: 21 Lbs (9.5 kg) Average charge time: 4-8 hours Performance/Charge: 36+ holes Lifetime: ca. 150+ charges	33Ah SLA Dim: 8 x 5 x 6 in (20 x 13 x 15 cm) Weight: 21 Lbs (9.5 kg) Average charge time: 4-8 hours Performance/Charge: 36+ holes Lifetime: ca. 150+ charges	35Ah SLA Dim: 8 x 5 x 6 in (20 x 13 x 15 cm) Weight: 25 Lbs (11 kg) Average charge time: 4-8 hours Performance/Charge: 27+ holes Lifetime: ca. 150+ charges	35/36Ah SLA Dim: 8 x 5 x 6 in (20 x 13 x 15 cm) Weight: 25 Lbs (11 kg) Average charge time: 4-8 hours Performance/Charge: 27-36 holes Lifetime: ca. 150+ charges	35/36Ah SLA Dim: 8 x 5 x 6 in (20 x 13 x 15 cm) Weight: 25 Lbs (11 kg) Average charge time: 4-8 hours Performance/Charge: 27-36 holes Lifetime: ca. 150+ charges	35/36Ah SLA Dim: 8 x 5 x 6 in (20 x 13 x 15 cm) Weight: 25 Lbs (11 kg) Average charge time: 4-8 hours Performance/Charge: 27+ holes Lifetime: ca. 150+ charges
Lithium Battery	12V 16Ah LI Dim: 7 x 5 x 4 in (17.8 x 12.7 x 10.2 cm) Weight: 5 Lbs (2.3 kg) Average charge time: 4-6 hours Performance/Charge: 54+ holes Lifetime: ca. 1000 charges	12V 16Ah LI Dim: 7 x 5 x 4 in (17.8 x 12.7 x 10.2 cm) Weight: 5 Lbs (2.3 kg) Average charge time: 4-6 hours Performance/Charge: 54+ holes Lifetime: ca. 1000 charges	12V 16Ah LI Dim: 7 x 5 x 4 in (17.8 x 12.7 x 10.2 cm) Weight: 5 Lbs (2.3 kg) Average charge time: 4-6 hours Performance/Charge: 54+ holes Lifetime: ca. 1000 charges	12V 16Ah LI Dim: 7 x 5 x 4 in (17.8 x 12.7 x 10.2 cm) Weight: 5 Lbs (2.3 kg) Average charge time: 4-6 hours Performance/Charge: 54+ holes Lifetime: ca. 1000 charges	12V 20Ah LI Dim: 7 x 5 x 4 in (17.8 x 12.7 x 10.2 cm) Weight: 6 Lbs (2.7 kg) Average charge time: 4-6 hours Performance/Charge: 36+ holes Lifetime: ca. 1000 charges	12V 20Ah LI Dim: 7 x 5 x 4 in (17.8 x 12.7 x 10.2 cm) Weight: 6 Lbs (2.7 kg) Average charge time: 4-6 hours Performance/Charge: 36+ holes Lifetime: ca. 1000 charges	12V 20Ah LI Dim: 7 x 5 x 4 in (17.8 x 12.7 x 10.2 cm) Weight: 6 Lbs (2.7 kg) Average charge time: 4-6 hours Performance/Charge: 36+ holes Lifetime: ca. 1000 charges
Battery Upgrade Options	33Ah @ \$20; 35Ah @ \$30; 16Ah LI @ \$350; 20Ah LI @ \$400;	35Ah @ \$10; 16Ah LI @ \$350; 20Ah LI @ \$400;	35Ah @ \$10; 16Ah LI @ \$350; 20Ah LI @ \$400;	16Ah LI @ \$350; 20Ah LI @ \$400;	LI @ \$300 (Special Promo)	LI @ \$400	LI @ \$400
Folded Dimensions (w/o wheels)	Length: 32 in (81.3 cm) Width: 22 in (55.9 cm) Height: 9 in (22.9 cm)	Length: 32 in (81.3 cm) Width: 22 in (55.9 cm) Height: 9 in (22.9 cm)	Length: 31 in (78.7 cm) Width: 19 in (48.3 cm) Height: 10 in (25.4 cm)	Length: 32 in (81.3 cm) Width: 19 in (48.3 cm) Height: 13.5 in (34.3 cm)	Length: 31 in (78.7 cm) Width: 22.5 in (57.2 cm) Height: 10 in (25.4 cm)	Length: 32 in (81.3 cm) Width: 22 in (55.9 cm) Height: 9 in (22.9 cm)	Length: 31 in (78.7 cm) Width: 22 in (55.9 cm) Height: 10.5 in (26.7 cm)
Unfolded Dimensions	Length: 42-50 in (107-127 cm) Width: 23 in (58.4 cm) Height: 35-45 in (89-114 cm)	Length: 42-50 in (107-127 cm) Width: 23 in (58.4 cm) Height: 35-45 in (89-114 cm)	Length: 40 in (101.6 cm) Width: 22 in (55.9 cm) Height: 38.5 in (97.8 cm)	Length: 46 in (116.8 cm) Width: 22 in (55.9 cm) Height: 39.5 in (100.3 cm)	Length: 42 in (106.7 cm) Width: 25 in (63.5 cm) Height: 36.5 in (92.7 cm)	Length: 42-50 in (107-127 cm) Width: 23 in (58.4 cm) Height: 35-45 in (89-114 cm)	Length: 42-50 in (107-127 cm) Width: 22.5 in (57.2 cm) Height: 35-45 in (89-114 cm)
Caddy Weight (no battery)	21 lbs (9.5 kg)	21 lbs (9.5 kg)	19 Lbs (8.6 kg)	22 lbs (10 kg)	23 lbs (10.5 kg)	22 lbs (10 kg)	23 lbs (10.5 kg)
Total Weight (var. battery)	26 - 46 Lbs (11.8 - 20.9 kg)	26 - 46 Lbs (11.8 - 20.9 kg)	24 - 44 Lbs (10.9 - 20 kg)	27 - 47 lbs (12.3 - 21.4 kg)	29 - 48 lbs (13.2 - 21.8 kg)	28 - 47 lbs (12.7 - 21.4 kg)	29 - 48 lbs (13.2 - 21.8 kg)
Speed	5.4 mi/h (8.6 km/h)	5.4 mi/h (8.6 km/h)	5.4 mi/h (8.6 km/h)	5.4 mi/h (8.6 km/h)	5.4 mi/h (8.6 km/h)	5.4 mi/h (8.6 km/h)	5.4 mi/h (8.6 km/h)
Control Functions	Manual Seamless Rheostat Cruise Control Battery Charge Indicator Power On/Off	Manual Seamless Rheostat Cruise Control Battery Charge Indicator Power On/Off USB Port 10, 20, 30 Distance Timer Deluxe Upper & Lower Bag Supports	Manual Seamless Rheostat Cruise Control Functions: Forward, Stop Timed Advance Function (10, 20, 30 M/Y) Battery charge indicator Power On/Off USB Port LCD Display/Speed Indicator	Manual Seamless Rheostat Cruise Control Functions: Forward, Stop Timed Advance Function (10, 20, 30 M/Y) Battery charge indicator Power On/Off USB Port LCD Display/Speed Indicator	Manual Seamless Rheostat Remote Control (range up to 100 yards) Functions: Forward, Reverse, Left, Right, Stop Timed advance function (10, 20, 30 m/y) Cruise Control Battery Charge Indicator, LCD Display USB Port Power On/Off	Manual Seamless Rheostat Remote Control (range up to 100 yards) Functions: Forward, Reverse, Left, Right, Stop Timed advance function (10, 20, 30 m/y) Cruise Control Battery Charge Indicator USB Port Power On/Off	Manual Seamless Rheostat Remote Control (range up to 100 yards) Functions: Forward, Reverse, Left, Right, Stop Timed advance function (10, 20, 30 m/y) Cruise Control Battery Charge Indicator USB Port Power On/Off
Distance/Range	12 mi (20 km)/36+ holes	12 mi (20 km)/36+ holes	12 mi (20 km)/36+ holes	15 mi (25 km)/45+ holes	10-12 mi (20 km)/27-36+ holes	10-12 mi (20 km)/27-36+ holes	15 mi (25 km)/45+ holes (LI)
Climbing Ability	30 degrees	30 degrees	30 degrees	30 degrees	30 degrees	30 degrees	30 degrees
Off-Power Free-Wheeling Mode	X	X	X	X	X	X	X
Down Hill Speed Adjustment					X	X	X
Maximum Load	77 lbs (35 kg)	77 lbs (35 kg)	77 1bs (35 kg)	77 lbs (35 kg)	77 lbs (35 kg)	77 Ibs (35 kg)	77 lbs (35 kg)
Charger	Input: 110-240V AC Output: 12V/3A-4A Trickle Charger	Input: 110-240V AC Output: 12V/3A-4A Trickle Charger	Input: 110-240V AC Output: 12V/2A-3A Trickle Charger	Input: 110-240V AC Output: 12V/2A-3A Trickle Charger	Input: 110-240V AC Output: 12V/3A-4A Trickle Charger	Input: 110-240V AC Output: 12V/3A-4A DC Trickle Charger	Input: 110-240V AC Output: 12V/3A-4A DC Trickle Charger
Motor	Power: 1 x 200 Watt (200 Watt) 12V DC Electric	Power: 1 x 200 Watt (200 Watt) 12V DC Electric	Power: 1 x 200 Watt (200 Watt) 12V DC Electric	Power: 1 x 200 Watt (200 Watt) 12V DC Electric	Power: 2 x 200 Watt (400 Watt) 12V DC Electric	Power: 2 x 200 Watt (400 Watt) 12V DC Electric	Power: 2 x 200 Watt (400 Watt) 12V DC Electric
Front Wheels	Airless, rubberized tread Tracking adjustment	Airless, rubberized tread Tracking adjustment	Airless, rubberized tread Tracking adjustment	Airless, rubberized tread Tracking adjustment	Airless, rubberized tread Tracking adjustment	Airless, rubberized tread Tracking adjustment	X8R
Rear Wheels	Airless, rubberized tread Quick-release mechanism	Airless, rubberized tread Quick-release mechanism	Airless, rubberized tread Quick-release mechanism	Airless, rubberized tread Quick-release mechanism	Airless, rubberized tread Quick-release mechanism Standard Anti-tip wheel assembly	Airless, rubberized tread Quick-release mechanism Standard Anti-tip wheel assembly	Airless, rubberized tread Quick-release mechanism Standard Anti-tip wheel assembly
Drive Train	Rear Wheel Drive Gear ratio (17:1)	Rear Wheel Drive Gear ratio (17:1)	Rear Wheel Drive Gear ratio (17:1)	Rear Wheel Drive Gear ratio (17:1)	Rear Wheel Drive Direct Drive Dual independent transmission Gear ratio (17:1)	Rear Wheel Drive Direct Drive Dual independent transmission Gear ratio (17:1)	Rear Wheel Drive Direct Drive Dual independent transmission Gear ratio (17:1)
Handle Height Adjustment	X	X	N/A	N/A	N/A	X	X
Materials	Aluminum/SS and ABS	Aluminum/SS and ABS	Aluminum/SS and ABS	Aluminum/SS and ABS	Aluminum/SS and ABS	Aluminum/SS and ABS	Aluminum/SS and ABS
Available Frame Colors	Oxidized Silver	Oxidized Silver Matte Black Glossy White	Oxidized Silver Matte Black Glossy White	Oxidized Silver Matte Black Glossy White	Oxidized Silver Matte Black Glossy White	Oxidized Silver Matte Black Glossy White	Oxidized Silver Matte Black Glossy White
Available Wheel Colors (retrofittable for older models)	Silver	Silver Black White	Silver (yellow inlays) Black (yellow inlays) White (yellow inlays)	Silver (yellow inlays) Black (yellow inlays) White (yellow inlays)	Silver (yellow inlays) Black (yellow inlays) White (yellow inlays)	Silver Black White	Silver Black White
Complimentary Accessories	Scorecard Holder Cup Holder Umbrella Holder Carrying Bag Seat	Scorecard Holder Cup Holder Umbrella Holder Carrying Bag Seat	Scorecard Holder Cup Holder Umbrella Holder Carrying Bag Seat	Scorecard Holder Cup Holder Umbrella Holder Carrying Bag Seat	Scorecard Holder Cup Holder Umbrella Holder Carrying Bag Seat	Scorecard Holder Cup Holder Umbrella Holder Carrying Bag Seat	Scorecard Holder Cup Holder Umbrella Holder Carrying Bag Seat
Optional Accessories	Rain Cover Sand Dispenser GPS Holder see "Special Offers" for seasonal promotions	Rain Cover Sand Dispenser GPS Holder see "Special Offers" for seasonal promotions	Rain Cover Sand Dispenser GPS Holder see "Special Offers" for seasonal promotions	Rain Cover Sand Dispenser GPS Holder see "Special Offers" for seasonal promotions	Rain Cover Sand Dispenser GPS Holder Remote Control Cliphanger see "Special Offers" for seasonal promotions	Rain Cover Sand Dispenser GPS Holder Remote Control Cliphanger see "Special Offers" for seasonal promotions	Rain Cover Sand Dispenser GPS Holder Remote Control Cliphanger see "Special Offers" for seasonal promotions
Introduced(year)	2011	2013	2009	2013	2006	2009	2015
Certifications	UL/FCC Charger	UL/FCC Charger	UL/FCC Charger	UL/FCC Charger	FCC/IC Remote System; UL/FCC Charger	FCC/IC Remote System; UL/FCC Charger	FCC/IC Remote System; UL/FCC Charger
Warranty	1 Year on Parts and Labor 1 Year on SLA Battery, 2 Years on LI	1 Year on Parts and Labor 1 Year on SLA Battery, 2 Years on LI	1 Year on Parts and Labor 1 Year on SLA Battery, 2 Years on LI	1 Year on Parts and Labor 1 Year on SLA Battery, 2 Years on LI	1 Year on Parts and Labor 1 Year on SLA Battery, 2 Years on LI	1 Year on Parts and Labor 1 Year on SLA Battery, 2 Years on LI	1 Year on Parts and Labor 1 Year on SLA Battery, 2 Years on LI
Packaging & Gross Weight (weight w/o battery)	Type: Cardboard Box/Styrofoam Dim: 33 x 25 x 12 in (83.8 x 63.5 x 30.5 cm) Gross Weight: 33 lbs (15 kg)	Type: Cardboard Box/Styrofoam Dim: 33 x 25 x 12 in (83.8 x 63.5 x 30.5 cm) Gross Weight: 33 lbs (15 kg)	Type: Cardboard Box/Styrofoam Dim: 35 x 21 x 13 in (89 x 53 x 33 cm) Gross Weight: 31 lbs (14 kg)	Type: Cardboard Box/Styrofoam Dim: 35 x 21 x 14 in (89 x 53 x 36 cm) Gross Weight: 32 lbs (14.5 kg)	Type: Cardboard Box/Styrofoam Dim: 35 x 24 x 15 in (89 x 61 x 38 cm) Gross Weight: 39 lbs (17.7 kg)	Type: Cardboard Box/Styrofoam Dim: 34 x 25 x 12 in (86 x 64 x 31 cm) Gross Weight: 36 lbs (16.4 kg)	Type: Cardboard Box/Styrofoam Dim: 34 x 28 x 14 in (86 x 71.1 x 35.6 cm) Gross Weight: 39 lbs (17.7 kg)